

# ONDULEUR SG-3KW



Efficiency	
Max. Efficiency	97.8%
European efficiency	96.8%
Inputs (PV)	
Max. input voltage	500V
Max. PV configuration (STC)	150%
Rated input voltage	360V
Max. Input current	15A
Max short circuit current	20A
Starting input voltage	70V
MPPT operating voltage range	50V-490V
Max. number of PV strings	1
No. of MPPTs	1
Outputs (network)	
Nominal AC active power	<b>3000W</b>
Max. AC apparent power	3300VA
Max. AC active power (PF=1)	3300W
Max. AC output current	15A
AC rated voltage	220V/230V, L+N+PE
AC voltage range (1)	160V-300V (Adjustable)
Nominal grid frequency	50Hz/ 60Hz
Network frequency range(2)	45Hz-55Hz/55Hz-65Hz (Adjustable)
THDI	<3% (Rated Power)
DC injection	<0.5%In
Power factor	>0.99 Rated power (Adjustable 0.8 LD-0.8 LG)
Protection	
DC switch	Yes
Anti-island protection	Yes
AC overcurrent protection	Yes
AC short circuit protection	Yes
DC reverse connection	Yes
Surge arrester	DC Type III (Optional) / AC Type III
Insulation control	Yes
Leakage current protection	Yes
General	
Typology	Transformerless
Environmental protection grade	IP65
Nocturnal self-consumption	<1W
Cooling mode	Natural cooling
Operating temperature range	-25°C-60°C
Relative humidity range	0-100%
Max. operating altitude	4000m
Noise (typical)	30dB
Dimensions (W*H*D)	320mm*344mm*137mm
Weight	6.5Kg
HMI & COM	
Display	Wireless & APP+LED, LCD (Optional)
Communication	Optional: WiFi / GPRS / RS485
Certification	
Safety	IEC62109-1/2
Net	IEC 61000-1/2/3/4, IEC 61727/62116, CEI 021
Warranty	5 /10 years (optional)

*\*The output voltage and frequency range may vary according to different grid codes.*

*\*Specifications are subject to change without notice.*

